

LIS009001735B2

(12) United States Patent

Padovani et al.

(10) Patent No.: US 9,001,735 B2

(45) **Date of Patent:** *Apr. 7, 2015

(54) METHOD AND APPARATUS FOR HIGH RATE PACKET DATA TRANSMISSION

(71) Applicant: **QUALCOMM Incorporated**, San

Diego, CA (US)

(72) Inventors: **Roberto Padovani**, San Diego, CA

(US); Paul E. Bender, La Jolla, CA (US); Peter J. Black, San Diego, CA (US); Matthew S. Grob, La Jolla, CA (US); Jurg K. Hinderling, San Diego,

CA (US); Nagabhushana T.

Sindhushayana, San Diego, CA (US); Charles E. Wheatley, III, Del Mar, CA

(US)

(73) Assignee: QUALCOMM Incorporated, San

Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: 13/710,099

(22) Filed: Dec. 10, 2012

(65) **Prior Publication Data**

US 2013/0094391 A1 Apr. 18, 2013 Related U.S. Application Data

(63) Continuation of application No. 11/540,286, filed on Sep. 29, 2006, now Pat. No. 8,351,372, which is a continuation of application No. 10/809,213, filed on Mar. 25, 2004, now Pat. No. 7,184,426, which is a

(Continued)

(51) **Int. Cl.**

H04W 4/00 (2009.01) **H04L 1/18** (2006.01)

(Continued)

(52) U.S. Cl.

(Continued)

(58) Field of Classification Search

None

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,018,663 A 1/1962 Dunlop 3,534,264 A 10/1970 Blasbalg et al. (Continued)

FOREIGN PATENT DOCUMENTS

BR 9607900 A 1/1998 BR 9607621 A 6/1998 (Continued)

OTHER PUBLICATIONS

3GPP TS 25.101 V6.10.0, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; User Equipment (UE) radio transmission and reception (FDD) (Release 6) Section 9.3, Dec. 2005.

(Continued)

Primary Examiner — Bob Phunkulh (74) Attorney, Agent, or Firm — Peng Zhu

(57) ABSTRACT

In a data communication system capable of variable rate transmission, high rate packet data transmission improves utilization of the forward link and decreases the transmission delay. Data transmission on the forward link is time multiplexed and the base station transmits at the highest data rate supported by the forward link at each time slot to one mobile station. The data rate is determined by the largest C/I measurement of the forward link signals as measured at the mobile station. Upon determination of a data packet received in error, the mobile station transmits a NACK message back to the base station. The NACK message results in retransmission of the data packet received in error. The data packets can be transmitted out of sequence by the use of sequence number to identify each data unit within the data packets.

38 Claims, 15 Drawing Sheets

